

SLIM PREMIUM

WALL SOUNDPROOFING FRAMELESS SYSTEM

SYSTEM
THICKNESS
38.2 mm



GENERAL CONSTRUCTION
SOUND REDUCTION INDEX
Rw = 57-62 dB

AIRBORNE
SOUND REDUCTION
IMPROVEMENT INDEX
▲ Rw = 12-11 dB



DESCRIPTION

The thinnest system for soundproofing partition walls in apartments, country houses and non-residential buildings. Quick and easy to install. The system ensures domestic noise insulation and maintains sound comfort. The main system elements are composite Sonoplat Combi panels and Tecsound membranes.

COMPONENTS

Material	Coefficient per 1 m ² *
SonoPlat Combi panel (1.2m x 0.6m x 22mm) 0.72m ²	1,4583
Tecsound SY 70 Membrane (5m x 1.22m x 3.7mm) 6.1m ²	0,1721
Sonetic vibroacoustic sealant, 310ml	0,2500
Vibration cushioning band V-100 (30m x 100mm x 4mm)	0,0450
Sound insulation polymer dowel (6mm x70mm) 100 pcs.	0,1700
SonoPlat band (40m x 50mm) w/o logo	0,0769
AcousticGyps soundproofing gypsum board (2m x 1.2m x 12.5mm) 2.4m ²	0,4583
Self-threading screw TC-Y 5x40 (300 pcs.)	0,0540

*Coefficients are advisory in nature, calculated empirically